



# xFitter Tutorial

Stefano Camarda (CERN)

July 8, 2016

# xFitter tutorial

- Introduction: PDFs and the xFitter framework (formerly HERAFitter)
- An example of xFitter usage:  
QCD analysis of W and Z boson production at the Tevatron
- Exercises



# PDFs in the LHC era


Factorisation theorem:

$$\sigma_{pp \rightarrow X} = \sum_{i,j} \int dx_1 dx_2 \underbrace{f_i^p(x_1, \mu)}_{\text{PDFs}} \underbrace{f_j^p(x_2, \mu)}_{\text{PDFs}} \underbrace{\otimes}_{\text{Partonic cross sections}} \underbrace{\sigma_{i,j}}_{\text{Partonic cross sections}}$$


- Cross section are calculated by convoluting short distance partonic reactions with Parton Distribution Functions (PDFs)
- Discovery of new exciting physics relies on precise knowledge of proton structure.
- PDFs are among the dominant uncertainties for the W mass measurement and  $gg \rightarrow H$  production

xFitter provides a framework for

- Investigation of various methodologies in PDF fits
- Assess the impact of new data on PDF
- Help the experiments to improve the sensitivity of new measurements to PDF



# Schematic of PDF fits



# Schematic of PDF fits

Open-source xFitter implementation of QCD analysis

arXiv:1410.4412

<http://xfitter.org>  
xFitter 1.2.2

Correlated uncertainties

Input data

Theory predictions

Partonic  
cross sections



PDF evolved  
at all scales

Cov Matrix,  
nuisance parameters

$\chi^2$  test

MINUIT

Minimisation (Fit)  
of the PDF  
parameters at the  
starting scale


APPLGRID, FastNLO

PDF parametrisation at  
the starting scale  $\sim 1$  GeV  
with  $\sim 20$  free parameters

QCDNUM  
DGLAP  
evolution

Various flexible parametrization forms




Result:  
 $f(x, Q^2)$   
at all scales



# QCD analysis of W and Z Tevatron data


[arXiv:1503.05221](https://arxiv.org/abs/1503.05221)

- This analysis provides an extensive example of usage of xFitter, and is a good reference for a typical phenomenological study that can be performed with xFitter
- Various PDF fitting techniques were used: MINUIT minimisation, Hessian profiling, Bayesian reweighting
- The paper provides detailed descriptions of the settings of a QCD analysis and of the  $\chi^2$  definition
- Various PDF parametrisation forms are explored
- All the plots in the paper are produced with xFitter




# Motivation

- Precise determination of the quark valence PDFs is essential for precision measurements at the LHC, like the W mass and the weak mixing angle, and also for searches of new physics
- DIS collider data provide better constraints on u-quark valence, and less constraints on d-quark valence



- The reason is the stronger coupling of photons to u-quark than d-quark





H1prelim-14-042,ZEUS-prel-14-007

# Motivation

- In proton-antiproton collisions, DY processes of W and Z production are valence-quark dominated
- They can be used to improve quark valence PDFs, and especially the d-quark type, which is less constrained by DIS collider data

Most sensitive observable is the W charge asymmetry








# Tevatron W and Z data sets

- 3 types of observables
  - Z  $d\sigma/dy$  (CDF and D0)
  - Lepton charge asymmetry in  $W \rightarrow l, \nu$  (D0)
  - W charge asymmetry (CDF and D0)

Fast theory predictions calculated  
with MCFM+APPLGRID



- Revised correlation model: uncertainties of data-driven corrections are treated as bin-to-bin uncorrelated (lepton ID, trigger, and charge efficiencies)
- Reasonable assumption: these corrections are influenced by stat noise

# PDF fit of Tevatron W and Z production

QCD fit at NLO of HERA I and Tevatron W, Z data

The PDF parametrisation at the starting scale  $Q^2 = 1.7 \text{ GeV}^2$  is optimised through a  $\chi^2$  scan

Start from a simple  
3-parameters functional form

Add exp, linear and  
quadratic terms

Stop when  
 $\Delta\chi^2 \leq 1$

$$f(x) = Ax^B(1-x)^C \times e^{Fx}(1 + Dx + Ex^2)$$

The optimal  
parametrisation has  
15 parameters

Needed additional freedom in  
the valence PDFs to fit the W  
data, exp terms preferred



Data set	Experiment	$\chi^2/\text{points}$
DIS	H1 - ZEUS	516/550
Z $d\sigma/dy$	D0	23/28
Z $d\sigma/dy$	CDF	32/28
W $\mu$ -asymmetry	D0	12/10
W asymmetry	CDF	14/13
W asymmetry	D0	8/14
Total $\chi^2/\text{dof}$		606/628

Good overall and  
partial  $\chi^2$  of the QCD fit

# Impact on d-quark valence PDF



- The impact of the Tevatron W, Z data is assessed by comparing PDFs extracted from a fit to only HERA I data
- Observed large impact on d-quark valence PDF, mainly driven by the measurements of W charge asymmetry

*Example of plots that can easily be produced with xFitter*



# W charge asymmetry, D0 and CDF

*Example of plots that can easily be produced with xFitter*





- The results of the PDF fit are illustrated with data/theory comparison plots

# Compatibility with global PDF sets

*xFitter is used to assess the compatibility between the data and various PDF set*

PDF	$\chi^2/\text{dof}$
CT10nlo	39/37
MMHT2014nlo	7/14
NNPDF3.0nlo	36/37



Good agreement between W asymmetry data and NLO predictions with global PDF sets

# Profiling global PDF sets

Assess the impact of the Tevatron data on the global PDF fits with a hessian profiling technique

Add the hessian PDF uncertainties as nuisance parameters  $\beta$  in the  $\chi^2$



Minimise the  $\chi^2$  and profile the PDF shifts  $\beta$  to the data

$$\chi^2(\beta_{\text{exp}}) \rightarrow \chi^2(\beta_{\text{exp}}, \beta_{\text{th}})$$

*xFitter is used to assess the impact of new data on already existing PDF sets*

Propagate the shifts and the reduction of the uncertainties to the PDFs

Also in this case observed a significant reduction of the d-valence PDF uncertainty



- 1 PDF fit to HERA I+II data
- 2 PDF fit and  $\alpha_s$  extraction from HERA jets data
- 3 LHAPDF analysis: PDF profiling
- 4 Plotting of LHAPDF6 files
- 5 Equivalence of  $\chi^2$  definitions

# xFitter tutorial loading...

Open a shell and do:

```
student@mcnet:~$ cd tutorial/xfitter
```

```
student@mcnet:~/tutorial/xfitter$ svn up
```



- Each of the five exercise is in a separate directory:

```
exercise1/  
exercise2/  
exercise3/  
exercise4/  
exercise5/
```

- You can find the xFitter manual, the README file, and this tutorial in doc/

```
doc/manual.pdf  
doc/README  
doc/tutorial.pdf
```

# General structure of the exercises

As a general rule, each exercise has:

- A README file, which contains all the commands to perform the exercise
- A input/ directory, with all the necessary input settings for running xFitter
- During the exercise, we will create a run/ directory, where we will run xFitter
- The results will be saved in the output/ directory, for further manipulation

On a shell type `xfitter` and press the Tab character twice

- `xfitter`: The main xFitter program, to perform PDF fits
- `xfitter-draw`: Graphical visualisation of the results
- `xfitter-process`: Post-fit or pre-fit manipulation of LHAPDF files
- `xfitter-config`: Provide compiler options to link xFitter as an external library

# Input configuration files for xFitter

In general, each time we want to run xFitter, we need to care about three configuration files:

- steering.txt
  - Running mode: PDF fit or LHAPDF analysis
  - List of data sets
  - PDF parametrisation
  - QCD Order, heavy flavour scheme
  - $\chi^2$  settings
- ewparam.txt
  - EW and SM parameters (mainly used for the DIS cross section)
- minuit.in.txt
  - Settings and commands for minuit
  - Fix and free parameters of the PDF parametrisation

# Exercise 1


## PDF fit

```
cd exercise1
```

# Exercise 1

- *purpose*: Learn the basic settings of a QCD analysis
- *data set*: HERA I+II inclusive DIS data
- *QCD order*: NNLO

# Schematic of a PDF fit



# Exercise 1 - Settings

The HERA I+II data sets are set in  
`input/steering.txt`

```
&InFiles
! Number of input files
  NInputFiles = 7

! Input files:

  InputFileNames(1) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCep_920.dat'
  InputFileNames(2) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCep_820.dat'
  InputFileNames(3) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCep_575.dat'
  InputFileNames(4) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCep_460.dat'
  InputFileNames(5) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCem.dat'
  InputFileNames(6) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_CCep.dat'
  InputFileNames(7) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_CCem.dat'
&End
```



# Exercise 1 - Settings

We will use the option `RunningMode = 'Fit'` in `input/steering.txt`

```
&xFitter
  RunningMode = 'Fit'
              ! 'Fit'                -- standard MINUIT-minimization of PDF and other parameters
              ! 'LHAPDF Analysis'    -- Evaluate input LHAPDF set uncertainties, chi2, profiling or reweighting
              !                      -- Requires &LHAPDF namelist to specify the set name. If PDFSTYLE is not
              !                      -- set to LHAPDFQO, LHAPDF or LHAPDFNATIVE, sets it to LHAPDF
              ! 'PDF Rotate'         -- performs PDF re-diagonalization. Requires theo.in files to operate
  ...
&End
```

The order in perturbative QCD is set in  
input/steering.txt

```
&xFitter
...
Order = 'NNLO'      ! 'LO', 'NLO' or 'NNLO', used for DGLAP evolution.
...
&End
```

The starting scale Q02 of the PDF parametrisation is set in `input/steering.txt`

```
&xFitter
...
  Q02      = 1.9 ! Evolution starting scale
...
&End
```

# Exercise 1 - Settings

The Heavy flavour scheme is set in  
input/steering.txt

&xFitter

```
...
! --- Scheme for heavy flavors
! --- HF_SCHEME = 'ZMVFNS'           : ZM-VFNS (massless) from QCDNUM,
! --- HF_SCHEME = 'ZMVFNS MELA'      : ZM-VFNS (massless) from MELA (N-space),
! --- HF_SCHEME = 'RT'               : Thorne-Roberts VFNS (massive)
! --- HF_SCHEME = 'RT FAST'          : Fast approximate TR VFNS scheme, usign k-factor
! --- HF_SCHEME = 'RT OPT'           : Thorne-Roberts VFNS (massive)
! --- HF_SCHEME = 'RT OPT FAST'      : Fast approximate TR VFNS scheme, usign k-factor
! --- HF_SCHEME = 'ACOT Full'        : ACOT - F.Olness Version (massive), using k-factors
! --- HF_SCHEME = 'ACOT Chi'         : ACOT - F.Olness Version (massive), using k-factors
! --- HF_SCHEME = 'ACOT ZM'          : ACOT - F.Olness Version (massless), using k-factors
! --- HF_SCHEME = 'FF'               : Fixed Flavour Number Scheme (qcdnum)
! --- HF_SCHEME = 'FF ABM'           : Fixed Flavour Number Scheme (ABM)
! --- HF_SCHEME = 'FF ABM RUNM'      : Fixed Flavour Number Scheme (ABM) using run mass def
! --- HF_SCHEME = 'FONLL-A'          : FONLL-A mass scheme provided by APFEL with pole masses (available)
! --- HF_SCHEME = 'FONLL-A RUNM OFF' : FONLL-A mass scheme provided by APFEL with MSbar masses running (available)
! --- HF_SCHEME = 'FONLL-A RUNM ON'  : FONLL-A mass scheme provided by APFEL with MSbar masses running (available)
! --- HF_SCHEME = 'FONLL-B'          : FONLL-B mass scheme provided by APFEL with pole masses (available)
! --- HF_SCHEME = 'FONLL-B RUNM OFF' : FONLL-B mass scheme provided by APFEL with MSbar masses running (available)
! --- HF_SCHEME = 'FONLL-B RUNM ON'  : FONLL-B mass scheme provided by APFEL with MSbar masses running (available)
! --- HF_SCHEME = 'FONLL-C'          : FONLL-C mass scheme provided by APFEL with pole masses (available)
! --- HF_SCHEME = 'FONLL-C RUNM OFF' : FONLL-C mass scheme provided by APFEL with MSbar masses running (available)
! --- HF_SCHEME = 'FONLL-C RUNM ON'  : FONLL-C mass scheme provided by APFEL with MSbar masses running (available)
! (Any of the FONLL schemes at LO is equivalent to the ZM-VFNS)

HF_SCHEME = 'RT OPT'
...
&End
```

# Exercise 1 - Settings

The PDF parameterisation is set in  
input/steering.txt

```
&xFitter
```

```
...
```

```
! PDF parameterisation style. Possible styles are currently available:
```

```
! 'HERAPDF' -- HERAPDF-like with uval, dval, Ubar, Dbar, glu evolved pdfs
```

```
! 'CTEQ'      -- CTEQ-like parameterisation
```

```
! 'CTEQHERA'  -- Hybrid: valence like CTEQ, rest like HERAPDF
```

```
! 'CHEB'      -- CHEBYSHEV parameterisation based on glu,sea, uval,dval evolved pdfs
```

```
! 'LHAPDFQO'  -- use lhpdf library to define pdfs at starting scale and evolve with local qcdnum para
```

```
! 'LHAPDF'    -- use lhpdf library to define pdfs at all scales
```

```
! 'LHAPDFNATIVE' -- use lhpdf library to access pdfs and alphas
```

```
! 'DDIS'      -- use Diffractive DIS
```

```
! 'BiLog'     -- bi-lognormal parameterisation
```

```
PDFStyle = 'HERAPDF'
```

```
...
```

```
&End
```

Convention for the HERAPDF-like PDF parametrisation

$$Ax^B(1-x)^C(1+Dx+Ex^2) - A'x^{B'}(1-x)^{C'}$$

# Exercise 1 - Settings

The starting values of the parameters are set in  
`input/minuit.in.txt`

```
set title
new 14p HERAPDF
parameters
  2  'Bg'    -0.061953    0.027133
  3  'Cg'    5.562367    0.318464
  7  'Aprig'  0.166118    0.028009
  8  'Bprig' -0.383100    0.009784
  9  'Cprig' 25.000000    0.000000
 12  'Buv'   0.810476    0.016017
 13  'Cuv'   4.823512    0.063844
 15  'Euv'   9.921366    0.835891
 22  'Bdv'   1.029995    0.061123
 23  'Cdv'   4.846279    0.295439
 33  'CUbar'  7.059694    0.809144
 34  'DUbar'  1.548098    1.096540
 41  'ADbar'  0.268798    0.008020
 42  'BDbar' -0.127297    0.003628
 43  'CDbar'  9.586246    1.448861

call fcn 3
*migrad 200000
*hesse
set print 3

return
```

The first number is the starting value, if the second number is set to 0, the parameter is fixed

# Exercise 1 - Settings

To do a real MINUIT minimisation fit (about 1000-10000 iterations):

```
*call fcn 3  
migrad 200000  
hesse
```

To run only 3 iterations:

```
call fcn 3  
*migrad 200000  
*hesse
```



## Exercise 1 - Run

# Setup a run directory

```
mkdir run
```

```
ln -s ~/xfitter/xfitter-1.2.2/datafiles run/datafiles
```

```
cp input/* run
```

# Run xFitter

```
cd run
```

```
xfitter
```

## Exercise 1 - Visualize the results

```
cd .. (or cd ~/tutorial/xfitter/exercise1)
```

```
xfitter-draw output
```

```
evince output/plots.pdf
```

To see the full list of plotting options do:

```
xfitter-draw --help
```

## Exercise 2

Simultaneous PDF fit and  $\alpha_s$   
extraction from HERA jets data

```
cd exercise2
```

- *purpose*: Learn the basics of an  $\alpha_s$  extraction
- *data set*: H1 jets data
- *QCD order*: NLO

## Exercise 2 - Settings

We add the H1 jets data to the list of data sets in `input/steering.txt`

```
&InFiles
! Number of input files
  NInputFiles = 12

! Input files:

  InputFileNames(1) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCep_920.dat'
  InputFileNames(2) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCep_820.dat'
  InputFileNames(3) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCep_575.dat'
  InputFileNames(4) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCep_460.dat'
  InputFileNames(5) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_NCem.dat'
  InputFileNames(6) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_CCep.dat'
  InputFileNames(7) = 'datafiles/hera/h1zeusCombined/inclusiveDis/1506.06042/HERA1+2_CCem.dat'

! H1 Jets:
  InputFileNames(8) = 'datafiles/hera/h1/jets/0706.3722/H1_InclJets_HighQ2_99-00.dat',
  InputFileNames(9) = 'datafiles/hera/h1/jets/0911.5678/H1_InclJets_LowQ2_99-00.dat',

  InputFileNames(10) = 'datafiles/hera/h1/jets/1406.4709/H1_NormTrijets_HighQ2_03-07.dat'
  InputFileNames(11) = 'datafiles/hera/h1/jets/1406.4709/H1_NormInclJets_HighQ2_03-07.dat'
  InputFileNames(12) = 'datafiles/hera/h1/jets/1406.4709/H1_NormDijets_HighQ2_03-07.dat'
&End
```

## Exercise 2 - Settings

For the H1 jets data we need to add also the files containing the uncertainty correlation matrices in `input/steering.txt`

```
&InCorr
! Number of correlation (statistical, systematical or full) files
NCorrFiles = 6

! Correlation files:
CorrFileNames(1) = 'datafiles/hera/h1/jets/1406.4709/H1_NormDijets_HighQ2_03-07___H1_NormDijets_HighQ2_03-07'
CorrFileNames(2) = 'datafiles/hera/h1/jets/1406.4709/H1_NormDijets_HighQ2_03-07___H1_NormTrijets_HighQ2_03-07'
CorrFileNames(3) = 'datafiles/hera/h1/jets/1406.4709/H1_NormInclJets_HighQ2_03-07___H1_NormDijets_HighQ2_03-07'
CorrFileNames(4) = 'datafiles/hera/h1/jets/1406.4709/H1_NormInclJets_HighQ2_03-07___H1_NormInclJets_HighQ2_03-07'
CorrFileNames(5) = 'datafiles/hera/h1/jets/1406.4709/H1_NormInclJets_HighQ2_03-07___H1_NormTrijets_HighQ2_03-07'
CorrFileNames(6) = 'datafiles/hera/h1/jets/1406.4709/H1_NormTrijets_HighQ2_03-07___H1_NormTrijets_HighQ2_03-07'

&End
```

The highest order in perturbative QCD for which the jets data are available is NLO, and is set in `input/steering.txt`

```
&xFitter
...
Order = 'NLO'      ! 'LO', 'NLO' or 'NNLO', used for DGLAP evolution.
...
&End
```

We have to free the  $\alpha_s(m_Z)$  parameter  
input/steering.txt

```
&ExtraMinimisationParameters
  name = 'alphas', 'fs', 'fcharm'
  value = 0.118 , 0.4, 0.
  step = 0.001 , 0.0 , 0. ! set to 0 to avoid minimisation
&End
```



## Exercise 2 - Settings

To do a real MINUIT minimisation fit (about 1000-10000 iterations):

```
*call fcn 3  
migrad 200000  
hesse
```

To run only 3 iterations:

```
call fcn 3  
*migrad 200000  
*hesse
```

## Exercise 2 - Run

# Setup a run directory

```
mkdir run
```

```
cp input/* run
```

```
ln -s ~/xfitter/xfitter-1.2.2/datafiles run/datafiles
```

# Run xfitter

```
cd run
```

```
xfitter
```

## Exercise 2 - Visualize the results

```
cd .. (or cd ~/tutorial/xfitter/exercise2)
```

```
xfitter-draw output
```

```
evince output/plots.pdf
```

# Exercise 3

## LHAPDF analysis

```
cd exercise3
```

- *purpose*: Learn how to include a new data set into an existing PDF set, without redoing a PDF fit
- *data set*: Tevatron  $W$ -boson charge asymmetry
- *QCD order*: NLO

Download PDF sets from LHAPDF

```
cd ~/tutorial/xfitter/pdfsets
```

LHAPDF is a convenient library for the generic interpolation of PDFs as functions of  $x$  and  $q^2$ . PDFs are saved as tables of PDF values at fixed points in  $x$  and  $q^2$ , and fast interpolation functions allow to access the PDFs at any other value.

## Exercise 3 - LHAPDF

```
cd ~/tutorial/xfitter/pdfsets  
lhapdf --pdfdir=./ install CT14nlo  
export LHAPATH='pwd'/:$LHAPATH
```

## Exercise 3 - Profiling methodology

The inclusion of new data into an existing PDF set can be done with a Hessian profiling technique

We define a  $\chi^2$  with theory uncertainties ( $\beta_{\text{th}}$  are the PDF uncertainties)

$$\chi^2(\beta_{\text{exp}}, \beta_{\text{th}}) = \chi_{\text{exp}}^2 + \chi_{\text{th}}^2 =$$
$$\sum_{i=1}^{N_{\text{data}}} \frac{\left( \sigma_i^{\text{exp}} + \sum_j \Gamma_{ij}^{\text{exp}} \beta_{j,\text{exp}} - \sigma_i^{\text{th}} - \sum_k \Gamma_{ik}^{\text{th}} \beta_{k,\text{th}} \right)^2}{\Delta_i^2}$$
$$+ \sum_j \beta_{j,\text{exp}}^2 + \sum_k \beta_{k,\text{th}}^2$$

- Find the  $\beta_{k,\text{th}}$  which minimised the  $\chi^2$  on the new data
- The fit is done by solving a system of linear equations
- Reinterpret the  $\beta_{k,\text{th}}$  shifts as optimisation of the PDFs



## Exercise 3 - Settings

The Tevatron  $W$  asymmetry data sets and correlation files are set in  
`input/steering.txt`

```
&InFiles
! Number of input files
  NInputFiles = 2

! Tevatron W asymmetry:
  InputFileNames(1) = 'datafiles/tevatron/cdf/wzProduction/0901.2169/CDF_W_asymmetry.dat'
  InputFileNames(2) = 'datafiles/tevatron/d0/wzProduction/1312.2895/D0_W_asymmetry.dat'
&End

&InCorr
! Number of correlation (statistical, systematical or full) files
  NCorrFiles = 1

! Correlation files:
  CorrFileNames(1) = 'datafiles/tevatron/d0/wzProduction/1312.2895/D0_W_asymmetry.corr'
&End
```

## Exercise 3 - Settings

We will use the option `RunningMode = 'LHAPDF Analysis'` in `input/steering.txt`

```
&xFitter
  RunningMode = 'LHAPDF Analysis'
              ! 'Fit'           -- standard MINUIT-minimization of PDF and other parameters
              ! 'LHAPDF Analysis' -- Evaluate input LHAPDF set uncertainties, chi2, profiling or reweighting
              !                  Requires &LHAPDF namelist to specify the set name. If PDFSTYLE is not
              !                  set to LHAPDFQO, LHAPDF or LHAPDFNATIVE, sets it to LHAPDF
              ! 'PDF Rotate'     -- performs PDF re-diagonalization. Requires theo.in files to operate
  ...
&End
```

PDFs are taken from LHAPDF, so there is no need to specify a parametrisation in `input/steering.txt`

```
&xFitter
  PDFStyle = 'LHAPDFNATIVE'
...
  AsymErrorsIterations = 20
...
&End
```

We have also enable the treatment of asymmetric PDF uncertainties with an iterative procedure

## Exercise 3 - Run

# Setup a run directory

```
mkdir run
```

```
cp input/* run
```

```
ln -s ~/xfitter/xfitter-1.2.2/datafiles run/datafiles
```

# Run xFitter

```
cd run
```

```
xfitter
```

## Exercise 3 - Visualize the results

```
cd .. (or cd ~/tutorial/xfitter/exercise3)

cp -r run/output .
xfitter-draw output:CT14nlo \
               profile:output:CT14nlo-profiled \
               --asym --bands --therr
evince plots/plots.pdf
```

## Exercise 3 - Produce a new PDF set

# Produce a new PDF in lhpdf6 format:

```
xfitter-process profile \  
    output/pdf_shifts.dat output/pdf_rotate.dat \  
    ../pdfsets/CT14nlo/ CT14nlo-TEVW
```

# Save the new PDF set into our lhpdf6 collection:

```
cp -r CT14nlo-TEVW/ ../pdfsets/
```

## Exercise 3 - Produce a new PDF set

*The new PDF set you have produced is ready to be used in the next Monte Carlo tutorials!*

To use it:

```
export LHAPATH=~/tutorial/xfitter/pdfsets/:$LHAPATH
```

# Exercise 4

## Plotting LHAPDF files

```
cd exercise4
```



- *purpose*: Direct visualisation of PDFs from LHAPDF6
- *language*: Python

## Exercise 4

# Take an output PDF from a previous exercise:

```
cp -r ../exercise1/output .
```

# Start the jupyter notebook:

```
jupyter notebook
```

# In the browser, select new → Python2

# Cut and paste from testPlot.py into the browser

# Execute commands with Alt+Enter

# Exercise 5

## Equivalence of $\chi^2$ representations

`cd exercise5`

- *purpose*: Test the equivalence of the nuisance parameters and covariance matrix  $\chi^2$  formulas
- *data set*: Tevatron  $W$  asymmetries

Nuisance parameters representation of the  $\chi^2$

$$\chi^2(\beta) = \sum_{i=1}^{N_{\text{data}}} \frac{\left( \sigma_i^{\text{exp}} + \sum_j \Gamma_{ij}^{\text{exp}} \beta_j - \sigma_i^{\text{th}} \right)^2}{\Delta_i^2} + \sum_j \beta_j^2$$

Covariance matrix representation of the  $\chi^2$

$$\chi^2(C) = \sum_{ij}^{N_{\text{data}}} (\sigma_i^{\text{exp}} - \sigma_i^{\text{th}}) C_{\text{tot} \, ij}^{-1} (\sigma_j^{\text{exp}} - \sigma_j^{\text{th}}).$$

The two representations are mathematically equivalent. In xFitter we can switch from one to the other.

To convert a covariance matrix into nuisance parameters representation:

```
&CovarToNuisance
  ! Global switch for using nuisance param representation for covariance mat.

  ! ----> change this setting
  LConvertCovToNui = .true.

  ! Tolerance -- zero means exact transformation
  Tolerance = 0.0

  ! The following lines allow to adjust error scaling properties (default: :M)
  DataName      = 'D0 W asymmetry 2013'
  DataSystType  = ':A'
&End
```

To convert a nuisance parameters (correlated systematic uncertainties) into covariance matrix representation:

```
&xFitter
...
CHI2SettingsName = 'StatScale', 'UncorSysScale', 'CorSysScale', 'UncorChi2Type', 'CorChi2Type'
! ----> change this setting
!Chi2Settings    = 'Poisson'   , 'Linear'   , 'Linear'   , 'Diagonal'   , 'Hessian'
Chi2Settings      = 'Poisson'   , 'Linear'   , 'Linear'   , 'Diagonal'   , 'Matrix'
...
&End
```

The first dataset has a covariance matrix provided, we test the conversion to nuisance parameter representation

```
diff input1-cov input1-nui
```

# Run the  $\chi^2$  test in xFitter:

```
ln -s ~/xfitter/xfitter-1.2.2/datafiles/ input1-cov/datafiles
ln -s ~/xfitter/xfitter-1.2.2/datafiles/ input1-nui/datafiles
cd input1-cov && xfitter && cd ..
cd input1-nui && xfitter && cd ..
```

# Compare results:

```
xfitter-draw input1-cov/output:covariance input1-nui/output:nuisance --outdir plots1
```



The second dataset has nuisance parameters provided in the form of systematic uncertainties, we test the conversion to covariance matrix representation

```
diff input2-nui input2-cov
```

```
# Run the  $\chi^2$  test in xFitter:
```

```
ln -s ~/xfitter/xfitter-1.2.2/datafiles/ input2-nui/datafiles
ln -s ~/xfitter/xfitter-1.2.2/datafiles/ input2-cov/datafiles
cd input2-nui && xfitter && cd ..
cd input2-cov && xfitter && cd ..
```

```
# Compare results:
```

```
xfitter-draw input2-nui/output:nuisance input2-cov/output:covariance
```

- xFitter is a framework for QCD analyses. It allows to perform PDF fits, sensitivity studies to PDFs, extraction of fundamental SM parameters, inclusion of new data on already existing PDF, and a variety of other phenomenological studies involving QCD and EW physics
- The program has many settings to address very different problems, nevertheless big efforts are made to keep the user interface accessible for simple and basic usage
- In this tutorial we have learned how to
  - Perform a PDF fit
  - Extract the value of the strong-coupling constant  $\alpha_s(m_Z)$
  - Include new data sets into existing PDF sets by mean of Hessian profiling
  - Perform basic manipulation and plotting of PDF sets
  - Test the equivalence of the  $\chi^2$  representations

- xFitter is a powerful tool to answer questions in QCD and PDF matters
- Which kind of questions?
  - How much can we improve our knowledge of PDFs by adding new data to the PDF fits?
  - What are the implications of using predictions based on different QCD theoretical model?
  - Which is the most effective strategy to reduce PDF uncertainties for searches for new physics, and for the determination of the fundamental parameters of the SM at hadron colliders?

Thanks for your attention